




# PRODUCT SPECIFICATION SHEET

## MODEL: PA15 Standard Fiberglass Media

### DESCRIPTION


The Filter Systems Model PA15 is a paint arresting product for use in a variety exhaust applications ranging from automotive spraybooth to industrial manufacturing. It consists of a gradually densified fiberglass and is pigmented on the air leaving side to aid in proper installation. The media is sold as pads or in 300' rolls.



### FEATURES

- ✓Weight of 15 GRAMS/SQ.FT.
- ✓Ideal for use in a variety of crossdraft applications.
- ✓98.66% average spray removal efficiency.
- ✓Meets the testing and performance requirements of NESHAP 40CFR63 6H.
- ✓Initial pressure drop of .02 @ 150 FPM.
- ✓All components rated UL 900 for flammability.
- ✓Paint holding capacity of 1.3 LBS/SQ.FT. of media.
- ✓Compression rolled and packed to reduce storage and shipping/handling costs.
- ✓Thermally stable to 212 degrees F.
- ✓Typically land-fillable (contains no known hazardous materials).
- ✓Available in rolls, or cut pads.

### TEST DATA



\*\*\*Actual test report available upon request.

### SELECTION CHART

PART #	SIZE	DESCRIPTION
PA15-2020	20"x20"	15Gram Fiberglass Exhaust Pads
PA15-2025	20"x25"	15Gram Fiberglass Exhaust Pads
PA15-2424	24"x24"	15Gram Fiberglass Exhaust Pads
PA15-203	20"x300'	15Gram Fiberglass Exhaust Roll
PA15-253	25"x300'	15Gram Fiberglass Exhaust Roll
PA15-303	30"x300'	15Gram Fiberglass Exhaust Roll
PA15-363	36"x300'	15Gram Fiberglass Exhaust Roll
PA15-413	41"x300'	15Gram Fiberglass Exhaust Roll
PA15-483	48"x300'	15Gram Fiberglass Exhaust Roll
PA15-603	60"x300'	15Gram Fiberglass Exhaust Roll
PA15-723	72"x300'	15Gram Fiberglass Exhaust Roll

Custom sizes available. Call for quote.

Distributed by:



45406 Trevor Ave.  
Lancaster, CA 93534  
TEL: 800-540-4 AIR  
FAX: 805-981-8675  
E-MAIL: sales@filtersystemsusa.com  
WEB: www.filtersystemsusa.com